Assembly instructions SLIDE

Important information for assembling our bathroom furniture.
Please read carefully before assembly and keep for future reference.

intarbad®

Assembly instructions SLIDE

Please check your bathroom furniture for possible damage before starting assembly. We cannot accept complaints about damage to furniture parts that have already been assembled!

The product image is for illustration purposes only and may differ from the model ordered.

Safety instructions:

- Assembly may only be carried out by qualified persons.
- The mounting hardware (screws, dowels) is only designed for solid walls with sufficient load-bearing capacity.
- Before drilling, make sure that there are no cables or pipes in the installation area of the wall.
- Electrical installations may only be carried out by a qualified electrician.
- Mirror cabinets/lighted mirrors with electrical installations must be at least 60 cm away from the bathtub or shower.

Installation sequence

❶ Light mirror

❷ WT base cabinet

❸ Washbasin

Light mirror installation instructions

Important information for installing our bathroom furniture. Please read carefully and keep for future reference before installation.

The product image is for illustration purposes only and may differ from the model you have ordered.

Assembly of illuminated mirrors

- Determine the position of the light mirror on the wall, mark the drilling points, drill, insert the dowels and screw in the screw hooks **(Fig. 15 – included in delivery)**.
- Please note: Electrical work may ONLY be carried out by a qualified electrician.
- The height can only be adjusted on the back of the mirror. To do this, the light mirror must be removed from the wall. Adjustment is made by turning the screw in the cabinet hanger.

Scope of delivery / mounting accessories Light mirror

Fig. 15
2 mounting hooks
2 dowels 8 mm

Assembly instructions for vanity units

Important information for assembling our bathroom furniture. Please read carefully before assembly and keep for future reference.

The product image is for illustration purposes only and may differ from the model you have ordered.

Assembly of vanity units

- Remove the pull-out from the cabinet **(Fig. 1)**.
- Determine the position of the vanity unit on the wall and mark the position of the mounting plates and drill holes. Attach the mounting plates as close to the wall as possible **(Fig. 3 and Fig. 9 – Scope of delivery)**.
- Remove the cover cap from the cabinet hanger on both sides **(Fig. 10 – included in delivery)**.
- Carefully place the washbasin cabinet on the mounting plates and then adjust the height and depth **(Fig. 3)**.
- Cover the cabinet hangers with the existing cover caps **(Fig. 10 – included in delivery)**.
- Fit the handle using the screws provided **(Fig. 11 – included in delivery)**.
- Handle the washbasin with care and do not place it on its edges. Carefully place the washbasin on the base cabinet.
- Have water connections installed by a qualified professional.
- Seal the washbasin to the wall and all areas where water could penetrate (especially around the washbasin) with silicone (transparent and solvent-free – not included in delivery) **(Fig. 4)**.
- Fit the pull-out and align it if necessary **(Fig. 2)**.
- Cover the adjustment screws in the pull-out with the cover caps provided **(Fig. 12 – included in delivery)**.

Assembly instructions for vanity units

Fig. 1 | Disassembly/assembly of pull-outs

Pull the pull-out unit of the base cabinet forwards – open

Hold the pull-out unit on the sides and lift it upwards with momentum (the pull-out unit is only clicked into place, so this will release the click mechanism
mechanism). Remove the pull-out (see video on our online page "Assembly videos").

Remove the body rails and attach the pull-out.

Push the pull-out unit all the way into the washbasin base cabinet and press down until you hear a "click" – it locks automatically.

Assembly instructions for vanity units

Fig. 2 | Height adjustment of the pull-outs

2a. Loosen the upper screw slightly so that the front can be adjusted.

2b. Adjust the height using the lower screw.

2c. Do this on both sides of the drawer frame. Then tighten the upper screw again and cover the adjusting screws with the cover caps provided **(Fig. 12 Scope of delivery)**.

Assembly instructions for vanity units

Fig. 3 | Assembly and adjustment of the cabinet hangers WT base cabinet

Assembly

Depth adjustment

Height adjustment

Fig. 4 | Washbasin installation / Sealing to the wall with silicone

Assembly instructions for vanity units

Scope of delivery / Assembly accessories

Fig. 9 Mounting plate
Screws 8 mm
8 mm dowels



Fig. 10
Per cabinet hanger 1
cover plate

Fig. 11
2-4 screws per handle,
depending on handle model

Fig. 12
Cover caps for adjustment screws in the drawer (2 per pull-out)